


B-RAD **BL SELECT**

NEW! Torque ranges up to 7000 Nm!

The newly designed B-RAD BL Select Series offers higher speed and longer battery life while incorporating a new torque display with buttons. The B-RAD BL Select allows the user to easily select the target torque. Patented Product.

- Now with digital torque settings, able to increase or decrease the value by 10 Nm
- Torque ranges up to 7000 Nm
- Equipped with the latest lithium-ion technology
- Suitable for pre-torque and service jobs where electricity or compressed air are not available
- Longer battery life as energy is used more efficiently



PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm) LOW	TORQUE (Nm) HIGH	RPM	WEIGHT (Kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
28264	B-RAD BL SELECT 700	0.75"	170	700	21.5	3.5	231	63	67	262
28266	B-RAD BL SELECT 1400	0.75"	270	1400	10.5	3.5	231	63	67	262
28267	B-RAD BL SELECT 1400-2	0.75"	270	1400	71	4.3	279	63	67	262
28268	B-RAD BL SELECT 2000	1.0"	400	2000	6	4.0	244	69	69	262
28269	B-RAD BL SELECT 2000-2	1.0"	400	2000	19.5	4.9	298	69	69	262
28270	B-RAD BL SELECT 4000	1.0"	800	4000	3	6.0	285	81	81	266
28271	B-RAD BL SELECT 4000-2	1.0"	800	4000	20	6.7	337	81	81	266
28272	B-RAD BL SELECT 7000	1.5"	1350	7000	2.1	8.8	295	95	95	272

Accuracy of +/-5%, Repeatability of +/-2%

RAD TORQUE SYSTEMS